



REBOKE 12000 TSI and REBOKE 12000 TSI GRAFITE

More capacity in
instantaneous seeds
treatment



Virtual catalog | English | April/2017

Stara



REBOKE 12000 TSI

The Reboke 12000 TSI is an agriculture chaser bin that makes the instantaneous treatment of seeds, offering ore agility and practicality in the planting activities. Its project and manufacturing was developed to allow easy visualization for the operator to the work that is occurring, allowing the treatment of seeds and the supply of the planter in a single machine, thereby, increasing the earnings in

productivity and profitability to the rural producer.

The Reboke 12000 TSI is the only one machine for seeds treatment in Brazil equipped with conveyer belt with straight slots in the center and fanfold in the laterals. This system significantly reduces the mechanical damage to the seeds, which may occur during the transportation of seed from the Reboke to the planter.



Motor responsible for the activation of the conveyer belt that transports the treated seeds.

Unload system with telescopic tube.

The conveyor belt is made of PVC with straight slots in the center and fanfold in the laterals.

Graphite system

The Reboke 1200 TSI has a system that fixes the graphite with the seed in the unload tube, offering a more homogeneous planting and with less wastage in the planter. The graphite system has a gear in stainless steel, responsible for moving the graphite to avoid galley formation.

TREATMENT SYSTEM

Product tanks

The Reboke 12000 TSI has three tanks in polyethylene with capacity for 35 liter each. Two tanks are to defensives for seeds protection. The other tank is thermal and sterilized for inoculants, offering more use and ensuring the survival of the bacteria (Rhizobium) for a longer period. The tanks for defensives and inoculants have an internal mixing system, to avoid that the product be hardened in the bottom of the tank.

Painel

The panel is easily visualized by the operator, offering a quick and practical adjustment of the treatment system.



Flex VT

It controls the treatment system from the machine that activates the independent actuators. Through the electronic panel is possible to adjust the flow, calibrate and start or stop the work.

REBOKE 12000 TSI GRAFITE



The reboke 12000 TSI Grafite is an agricultural chaser bin that performs the instantaneous application of graffiti on the seeds, ensuring that the seed have its flow during the planting. The Reboke 12000 TSI Grafite keep the main characteristics from the Reboke 12000 TSI.



Technical Specifications

Model
Reboke 12000 TSI
Height
3.520mm
Supply height
4.600mm
width
3.399mm
Length
6.247mm
Approximated weight
4.480kg
Tank capacity
12m ³
Seeds treatment capacity
Until 350kg/min*
Tires
18.4" x 34" / 23.1" x 26"
Seeds treatment of the recipient
35 liters
Dosage rate of inoculant
130 to 2000ml/min
Dosage rate of defensive
130 to 4000ml/min

* According to the type of product and defensives dosage.



Technical Specifications

Model
Reboke 12000 TSI Grafite
Height
3.520mm
Supply height
4.600mm
width
3.399mm
Length
6.247mm
Approximated weight
4.300kg
Tank capacity
12m ³
Seeds treatment capacity
Until 350kg/min
Tires
18.4" x 34" / 23.1" x 26"
dosage rate of graphite
100 to 2.500g/min