



The central dashboard provides all the essential information



Neatly arranged control levers in the right console

AGROLUX

100 / 90

FUNCTION MEETS CONTEMPORARY DESIGN.

AGROLUX 100 / 90

Versatile and extremely reliable.

The tractors of the Agrolux 90/100 series are simple, efficient and reliable tractors made to deliver the best performance and productivity in the 80-100 hp class. While functional, these tractors also boast advanced design and technology. The range is powered by an SDF 1000 Series engine. Setting these engines apart is a mixed oil/water cooling system and a mechanical high pressure injection system. The transmissions equipping the Agrolux features intelligently spaced gear ratios to cater for a wide range of different applications.

●: standard O: optional -: not available

The technical data and pictures are guideline only. Committed to delivering a product more and more in line with your needs, DEUTZ-FAHR reserves the right to update the specifications of its machines at any time.

MACHINE SPECIFICATIONS		AGROLUX 100	AGROLUX 90
ENGINE			
Manufacturer		SDF	SDF
Model		1000.4 WT	1000.4 WT
Emission		Stage II	Stage II
Cylinders/Displacement	n°/cc	4/4000	4/4000
Intake		Turbo	Turbo
Max. power (2000/25/CE)	kW/HP	70/96	64.6/87
Maximum torque	Nm	375	344
Air filter with dust ejector		●	●
Exhaust silencer on cab A-pillar		-	-
Fuel tank capacity	litres	100	100
TRANSMISSION			
Number of speeds (With super-creeper)		20+20	20+20
Minimum speed with supercreeper gear	km/h	0.39	0.39
Maximum speed	km/h	40	40
PTO			
Rear PTO	rpm	540/1000	540/1000
Ground Speed PTO		O	O
AXLES AND BRAKES			
2WD equipment		O	O
4WD front axle with brakes		●	●
Front wheel drive engagement		Mechanical	Mechanical
Front and rear differential lock engagement		Mechanical	Mechanical
Hydrostatic steering with independent pump		●	●
HYDRAULIC SYSTEM AND LIFT			
Fixed displacement pump flow (standard/optional)	l/min	56	56
Auxiliary rear mechanical distributors	n°	1/2/3	1/2/3
Rear lift control (Mechanical/Electronic)		●	●
Maximum rear lift capacity	kg	4200	4200
Maximum front lift capacity (optional)	kg	-	-
DRIVING POSITION			
Straddle operator's area		●	●
Safety frame		●	●
Side mounted levers		●	●
DIMENSIONS AND WEIGHTS			
Width (min.-max.)	mm	2050-2250	2050-2250
Wheelbase (4WD/2WD)	mm	2340/2360	2340/2360
Total unladen weight (min.-max.)	kg	3200	3200
Maximum permissible total weight	kg	6200	6200