



FRUTTETO³

■ STAGE III A

90 | 100



SAME

		90	100
ENGINE			
Emissions		Stage III A	Stage III A
Manufacturer		SDF	SDF
Cylinders/Capacity	No./cm ³	4/4000	4/4000
Intake		Turbo Intercooler	Turbo Intercooler
Max. homologated power (2000/25/EC) at 2200 rpm	kW/hp	63/85	71/96
Max. torque at 1600 rpm	Nm	345	373
Electronic engine management		•	•
Fuel tank (standard/optional)	litres	54/40	54/40
SHUTTLE			
Mechanical synchronised shuttle		•	•
Hydraulic power shuttle with Stop&Go system		•	•
MECHANICAL GEARBOX			
5 speed gearbox		•	•
Number of speeds with underdrive and supercreeper gear	n°	30+15	30+15
POWERSHIFT GEARBOX			
5 speed gearbox		•	•
Number of speeds with underdrive and supercreeper gear	n°	45+45	45+45
Powershift number of speeds	n°	3	3
REAR PTO			
Electro-hydraulically engaged		•	•
PTO 540		•	•
PTO 540/540ECO		o	o
PTO 540/1000		o	o
Ground speed PTO		o	o
FRONT PTO			
Electro-hydraulically engaged		•	•
PTO 1000		o	o
FRONT AND REAR AXLE			
Four wheel drive electro-hydraulically engaged		•	•
Electro-hydraulically engaged differential lock		•	•
BRAKES AND STEERING			
Multi-disc wet brakes on all four wheels		•	•
Independent parking brake		•	•
Hydraulic trailer braking		•	•
Hydrostatic steering with independent pump		•	•
Steering angle	degrees	55	55
HITCH			
Mechanical rear hitch		•	•
Electronic rear hitch		•	•
Rear hitch capacity	kg	2800	2800
Front hitch		o	o
Front hitch capacity	kg	1500	1500
HYDRAULIC SYSTEM			
Pump output	l/min	54	54
Hydraulic system with dual pump	l/min	33+25	33+25
Rear hydraulic auxiliary valves	N°	3	3
Mid-mounted auxiliary valves	N°	2	2
OPERATOR PLATFORM			
Suspended on silent-block mounts		•	•
Folding ROPS		•	•
CAB			
Suspended on silent-block mounts		•	•
Folding ROPS		•	•
Air conditioning		o	o

		90	100
DIMENSIONS AND WEIGHTS			
Standard rear tyres		380/70R24	380/70R24
Max. length without rear linkage	mm	3338	3363
Width (min./max.)	mm	1478-1988	1618-2018
Max height at ROPS	mm	2380	2405
Max. height at cab	mm	2380	2405
Ground clearance	mm	225	250
Wheelbase	mm	2120	2120
Front track (min.-max.)	mm	1282-1442	1316-1516
Rear track (min.-max.)	mm	1277-1589	1179-1579
Turning circle	mm	3700	3700
Max. weight with ROPS	kg	2780	2780
Max. weight with cab	kg	3000	3000
Maximum loading capacity	kg	5000	5000

• STD o OPT - Not available

*South African standard specifications 2026

1) The above configuration is intended as general information.

2) The right to make modifications is reserved. Please always consult your SAME authorized importer as the sole source of current information on our vehicle's technical features.

3) All pictures shown are for illustration purposes only. Actual product may vary due to product enhancements.



SAME