



EXPLORER NATURAL

■ STAGE III

95 | 105 | 115 | 125



SAME

EXPLORER NATURAL

		95	105	115	125
ENGINE					
Model		FARMotion 45			
Emission level		Stage III			
Cylinders/Displacement	n°/cc	4/3849			
Bore/Stroke	mm	103/115.5			
Turbo Intercooler		•			
Common Rail injection	bar	2000			
Max. power (ECE R120)	kW/HP	70/95	78/106	85/116	93/126
Power at rated engine speed (ECE R120)	kW/HP	66.4/90	74/101	80.6/110	88.2/110
Max. torque	Nm	389	433	472	517
Engine speed at maximum torque	Nm	1400			
Electronic engine control		•			
PowerCore air filter		•			
Fuel tank capacity		145			
AdBlue tank capacity	l	10			
EAT	System	DOC+DPF+SCR			
TRANSMISSION					
SDF transmission	Type	T4330	T4350	T5350	
Gearbox	n°	5 gears x 2 or 4 ranges			
MECHANICAL SHUTTLE					
Shuttle	Type	Mechanical with lever under steering wheel			
N° of speed (4 ranges)	n°	20+20			
N° of speed with Hi-Lo (2 ranges)	n°	20+20 Hi-Lo			
N° of speed with Hi-Lo (4 ranges)	n°	40+40 Hi-Lo			
POWERSHUTTLE					
PowerShuttle	Type	Hydraulic with lever under steering wheel			
Adjust. Response of PowerShuttle		5 different setting			
N° of speed (4 ranges)	n°	20+20			
N° of speed with Hi-Lo (2 ranges)	n°	20+20 Hi-Lo			
N° of speed with Hi-Lo (4 ranges)	n°	40+40 Hi-Lo			
Stop&Go		•			
ComfortClutch		•			
PTO					
Electrohydraulic engagement		•			
540/540ECO		•		-	
540/1000*		o		-	
540/540ECO/1000/1000ECO		-		•	
LIFT					
Mechanical rear lift		•		-	
Mechanical rear lift with EasyLift		o		-	
Electronic rear lift		-		•	
Rear lifting capacity (STD)	kg	3600			
Rear lifting capacity (OPT)	kg	4525		5410	
HYDRAULICS					
Pump flow	l/min	68			
Rear spool valves	n°	2/3			
BRAKES					
4 wheel braking		•			
Mechanical parking brake		•			
Hydraulic trailer brake		o			
FRONT AXLE					
Front axle	Size	1.5		2	
Steering angle	degrees	50		55	
Electrohydraulic 4WD engagement		•			
Electrohydraulic Diff. Lock engagement		•			
CAB					
4 pillar cab		•			
Standard roof		•			
High visibility roof - FOPS		o			
Hydro Silent-Block suspension		•			
Manual A/C		•			
Mechanical suspended seat		•			
Pneumatic suspended seat		o			
Passenger seat		o			
External controls for PTO and lift		o			
Radio		•			

		95	105	115	125
DIMENSIONS AND WEIGHTS					
With front tyre	Size	420/70 R24		440/65 R28	
With rear tyre	Size	480/70 R34		540/65 R38	
Wheelbase	mm	2400			
Max. length	mm	4268			
Total height	mm	2718		2743	2768
Width	mm	2051		2205	2325
Centre rear axle – cab	mm	1968			
Weight	kg	4000		4350	4350
Front admissible load	kg	2900		3000	3000
Rear admissible load	kg	3700		5000	5000
Total admissible load	kg	6500		7500	7500

- STD
- OPT
- not available
- * via dealer.

*South African standard specifications 2026

1) The above configuration is intended as general information.

2) The right to make modifications is reserved. Please always consult your SAME authorized importer as the sole source of current information on our vehicle's technical features.

3) All pictures shown are for illustration purposes only. Actual product may vary due to product enhancements.





Proudly imported by Kempston Agri.